

HIT-HY 100

Safety information for 2-Component-products

Issue date: 01/02/2022

Revision date: 01/02/2022

Supersedes: 13/11/2018

Version: 3.1

SECTION 1: Kit identification

1.1 Product identifier

Trade name

HIT-HY 100



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360

Label elements

GHS CA labelling

Hazard pictograms (GHS CA)



GHS07

GHS08

Signal word (GHS CA)

Danger

Hazardous ingredients

methacrylates, dibenzoyl peroxide, boric acid

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H360 - May damage fertility or the unborn child.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information


2-Component-foilpack, contains:

Component A: Urethane methacrylate resin, inorganic filler

Component B: Dibenzoyl peroxide, phlegmatized

HIT-HY 100

Safety information for 2-Component-products



Name	General description	Quantity	Unit	Classification (GHS CA)
HIT-HY 100, A		1	pcs (pieces)	Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 1B, H360
HIT-HY 100, B		1	pcs (pieces)	Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters
Notify authorities if liquid enters sewers or public waters

Storage conditions

Keep cool. Protect from sunlight.

Precautions for safe handling

Wear personal protective equipment
Avoid contact with skin and eyes
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
Provide good ventilation in process area to prevent formation of vapour

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation
Mechanically recover the product
Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition
Direct sunlight

Incompatible products

Strong bases
Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact

Rinse immediately with plenty of water
Remove contact lenses, if present and easy to do. Continue rinsing.
Obtain medical attention if pain, blinking or redness persists

First-aid measures after ingestion

Rinse mouth
Get medical advice/attention.
Do not induce vomiting
Obtain emergency medical attention

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.
Allow affected person to breathe fresh air
Allow the victim to rest

First-aid measures after skin contact

Wash contaminated clothing before reuse.
Wash with plenty of water/...
If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures general

Take off immediately all contaminated clothing.
Never give anything by mouth to an unconscious person
If you feel unwell, seek medical advice (show the label where possible)

Symptoms/effects after eye contact

May cause severe irritation

Symptoms/effects after skin contact

May cause an allergic skin reaction.

HIT-HY 100

Safety information for 2-Component-products

Other medical advice or treatment

Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions

Use water spray or fog for cooling exposed containers
Exercise caution when fighting any chemical fire
Prevent fire fighting water from entering the environment

Protection during firefighting

Self-contained breathing apparatus
Do not enter fire area without proper protective equipment, including respiratory protection

Hazardous decomposition products in case of fire

Thermal decomposition generates :
Carbon dioxide
Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 02/01/2022

Revision date: 02/01/2022

Supersedes: 11/13/2018

Version: 3.1

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 100, B
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended uses and restrictions	For professional use only
Recommended use	Composite mortar component for fasteners in the construction industry

1.3. Supplier

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Warning

Hazard statements (GHS CA)

Precautionary statements (GHS CA)

H317 - May cause an allergic skin reaction.
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂) / quartz flour, 1%≤conc respirable crystalline silica<10% / silicon (di)oxide (quartz), 1%≤conc respirable crystalline silica<10%	(CAS-No.) 14808-60-7	40 – 60	Carc. 1A, H350
dibenzoyl peroxide	dibenzoyl peroxide; benzoyl peroxide	(CAS-No.) 94-36-0	5 – 10	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
---------------------------	---

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Protection during firefighting

Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Spilled material may present a slipping hazard.

6.2. Methods and materials for containment and cleaning up

For containment

Collect spillage.

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

Other information

Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep cool. Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure adequate ventilation.

Environmental exposure controls

Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	≈ 6
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Decomposition temperature	≈ 65 °C SADT
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Vapour pressure at 50 °C	No data available
Relative density	No data available
Density	2 g/cm ³ DIN 66137-2
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	35000 mm ² /s
Viscosity, dynamic	70 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified pH: ≈ 6
Serious eye damage/irritation	Not classified pH: ≈ 6
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 100, B

Viscosity, kinematic	35000 mm ² /s
----------------------	--------------------------

Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
--	----------------

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazardous to the aquatic environment, long-term (chronic)

Not classified

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	0.001 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.71
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)

12.2. Persistence and degradability

HIT-HY 100, B	
Persistence and degradability	Not established.
Quartz (SiO₂) (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 100, B	
Bioaccumulative potential	Not established.
Quartz (SiO₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
dibenzoyl peroxide (94-36-0)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	3.71
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.4. Mobility in soil

Quartz (SiO₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.71

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)
Transport document description			
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III
14.3. Transport hazard class(es)			
9	9	9	9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport


Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3

HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Orange plates



Tunnel restriction code (ADR)

-

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-HY 100, B	
Canada DSL & NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)
Quartz (SiO₂) (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
dibenzoyl peroxide (94-36-0)	
Listed on the Canadian DSL (Domestic Substances List)	

15.2. International regulations

Quartz (SiO₂) (14808-60-7)	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	
dibenzoyl peroxide (94-36-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

SECTION 16: Other information

Issue date	02-01-2022
Revision date	02-01-2022
Supersedes	11-13-2018

Indication of changes:



HIT-HY 100, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Section	Changed item	Change	Comments
14	Transport information	Modified	

Other information: None.

Full text of H-statements:

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 02/01/2022

Revision date: 02/01/2022

Supersedes: 11/13/2018

Version: 2.3

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 100, A
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended uses and restrictions	For professional use only
Recommended use	Composite mortar component for fasteners in the construction industry

1.3. Supplier

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H360 - May damage fertility or the unborn child.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂) / quartz flour, 1%≤conc respirable crystalline silica<10% / silicon (dioxide) (quartz), 1%≤conc respirable crystalline silica<10%	(CAS-No.) 14808-60-7	25 – 40	Carc. 1A, H350
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	1,2-propanediol, 2-methyl, monomethacrylate / 2-propenoic acid, 2-methyl-, 2-hydroxymethylethyl ester / 2-propenoic acid, 2-methyl-, monoester with 1,2-propanediol / hydroxypropyl methacrylate / methacrylic acid, ester with 1,2-propanediol / methacrylic acid, monoester with 1,2-propanediol / propylene glycol monomethacrylate / ROCRYL 410	(CAS-No.) 27813-02-1	5 – 10	Eye Irrit. 2A, H319 Skin Sens. 1, H317
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester		(CAS-No.) 2082-81-7	5 – 10	Skin Sens. 1B, H317
1,1,1-Trimethylolpropane trimethacrylate		(CAS-No.) 3290-92-4	1 – 2.5	Not classified
1,1'-(p-tolylimino)dipropan-2-ol	DiPpT	(CAS-No.) 38668-48-3	1 – 2.5	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319
boric acid	boric acid basilit B / boracic acid / boric acid / boric acid (H ₃ -BO ₃) / borofax / boron trihydroxide / dr.'s 1 flea terminator DF / dr.'s 1 flea terminator DFPBO / dr.'s 1 flea terminator DT / dr.'s 1 flea terminator DTPBO / E284 / epa pesticide code 011001 / flea prufe / LUCHEM AT / OPTIBOR NF / OPTIBOR SP / OPTIBOR SQ / OPTIBOR TG / OPTIBOR TP / orthoboric acid / ortho-boric acid / sassolite / super flea eliminator / three elephant / trihydroxyborone	(CAS-No.) 10043-35-3	0.1 – 1	Repr. 1B, H360
4-tert-butylpyrocatechol	(dimethyl-1,1 ethyl)-4 dihydroxy-1,2 benzene / 1,2-Benzenediol, 4-(1,1-dimethylethyl)- / 4-(1,1-dimethylethyl)-1,2-benzenediol / 4,6-butylcatechol / 4-TBC / 4-t-butylcatechol / 4-t-butylpyrocatechol / 4-tert-butyl-1,2-benzenediol / 4-tert-butyl-1,2-dihydroxybenzene / 4-tert-butylcatechol / 4-tert-butylpyrocatechol / 4-tert-butylpyrocatechin / 4-tertiary butylcatechol / 4-tertiary-butyl-1,2-benzediol / 4-tertiary-butyl-1,2-dihydroxybenzene / 4-tertiary-butylcatechin / 4-tertiary-butylcatechol / 4-tertiary-butylpyrocatechol / para-tertiary-butylcatechol / para-tertiary-butylpyrocatechol / p-t-butyl catechol / p-t-butylpyrocatechol / pyrocatechol, 4-tert-butyl- / synox TBC / TBC (=4-tert-butylcatechol)	(CAS-No.) 98-29-3	0.1 – 1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Other information

Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep cool. Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure adequate ventilation.

Environmental exposure controls

Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Grey
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Vapour pressure at 50 °C	No data available
Relative density	No data available
Density	1.74 g/ml DIN 66137-2
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	40.23 mm ² /s
Viscosity, dynamic	70 HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

boric acid (10043-35-3)	
LD50 oral rat	2660 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >2600 mg/kg bodyweight; Rat; Experimental value)
LD50 oral	2660 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Rabbit; Experimental value; FIFRA (40 CFR)
ATE CA (oral)	2660 mg/kg bodyweight

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CA (oral)	25 mg/kg bodyweight

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg
ATE CA (oral)	10066 mg/kg bodyweight

4-tert-butylpyrocatechol (98-29-3)	
LD50 oral rat	815 mg/kg bodyweight (Rat; Lethal; ECHA)
LD50 oral	2820 mg/kg
LD50 dermal rat	1331 mg/kg bodyweight (Rat;Lethal; ECHA)
LD50 dermal	630 mg/kg
ATE CA (oral)	815 mg/kg bodyweight
ATE CA (Dermal)	630 mg/kg bodyweight

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

1,1,1-Trimethylolpropane trimethacrylate (3290-92-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 3000 mg/kg

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

HIT-HY 100, A	
Viscosity, kinematic	40.23 mm ² /s

Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

boric acid (10043-35-3)	
LC50 - Fish [1]	447 mg/l
LC50 - Fish [2]	79 ppm (96 h; Salmo gairdneri (Oncorhynchus mykiss); Hard water)
EC50 - Crustacea [1]	658 – 875 mg/l (48 h; Daphnia magna)
EC50 - Crustacea [2]	19.7 mg/l (336 h; Daphnia magna)
ErC50 algae	290 mg/l
NOEC chronic fish	2.1 mg/l
BCF - Fish [2]	< 0.1 (60 days; Oncorhynchus tshawytscha; Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-1.09 (Experimental value; EU Method A.8: Partition Coefficient; 22 °C)

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LC50 - Fish [1]	≈ 17 mg/l
LC50 - Other aquatic organisms [1]	245 mg/l
EC50 - Crustacea [1]	28.8 mg/l
Partition coefficient n-octanol/water (Log Kow)	2.1
NOEC (acute)	57.8 mg/l

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (chronic)	20 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.1
NOEC (acute)	7.51 mg/l

4-tert-butylpyrocatechol (98-29-3)	
LC50 - Fish [1]	0.12 mg/l (96 h, Danio rerio, Lethal, ECHA)
ErC50 algae	10.17 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	1.98 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.37 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

1,1,1-Trimethylolpropane trimethacrylate (3290-92-4)	
LC50 - Fish [1]	2 mg/l
ErC50 algae	3.88 mg/l
NOEC chronic fish	0.138 mg/l
NOEC chronic crustacea	0.177 mg/l
BCF - Fish [2]	366 l/kg
Partition coefficient n-octanol/water (Log Kow)	4.39
Partition coefficient n-octanol/water (Log Pow)	3.53

12.2. Persistence and degradability

HIT-HY 100, A	
Persistence and degradability	Not established.

Quartz (SiO₂) (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Biodegradation	84 %

4-tert-butylpyrocatechol (98-29-3)	
Persistence and degradability	Not readily biodegradable in water.
ThOD	2.4 g O ₂ /g substance

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 100, A	
Bioaccumulative potential	Not established.

Quartz (SiO₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

boric acid (10043-35-3)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
BCF - Fish [2]	< 0.1 (60 days; Oncorhynchus tshawytscha; Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-1.09 (Experimental value; EU Method A.8: Partition Coefficient; 22 °C)

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1

4-tert-butylpyrocatechol (98-29-3)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	1.98 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.37 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
BCF - Fish [1]	≤ 100

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)

1,1,1-Trimethylolpropane trimethacrylate (3290-92-4)	
BCF - Fish [2]	366 l/kg
Partition coefficient n-octanol/water (Log Pow)	3.53
Partition coefficient n-octanol/water (Log Kow)	4.39

12.4. Mobility in soil

Quartz (SiO₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

boric acid (10043-35-3)	
Ecology - soil	No (test)data on mobility of the substance available. May be harmful to plant growth, blooming and fruit formation.
Partition coefficient n-octanol/water (Log Pow)	-1.09 (Experimental value; EU Method A.8: Partition Coefficient; 22 °C)

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1

4-tert-butylpyrocatechol (98-29-3)	
Surface tension	No data available (test not performed)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.37 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	1.98 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)

1,1,1-Trimethylolpropane trimethacrylate (3290-92-4)	
Partition coefficient n-octanol/water (Log Pow)	3.53
Partition coefficient n-octanol/water (Log Kow)	4.39

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Ecology - waste materials

Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID /

ADR	IMDG	IATA	RID
14.1. UN number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport
No data available

Transport by sea
No data available

Air transport
No data available

Rail transport
No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-HY 100, A	
Canada DSL & NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)
Quartz (SiO₂) (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Listed on the Canadian DSL (Domestic Substances List)	

HIT-HY 100, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)
Listed on the Canadian DSL (Domestic Substances List)
4-tert-butylpyrocatechol (98-29-3)
Listed on the Canadian DSL (Domestic Substances List)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)
Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Quartz (SiO₂) (14808-60-7)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
boric acid (10043-35-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
1,1'-(p-tolyimino)dipropan-2-ol (38668-48-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
4-tert-butylpyrocatechol (98-29-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
1,1,1-Trimethylolpropane trimethacrylate (3290-92-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Issue date	02-01-2022
Revision date	02-01-2022
Supersedes	11-13-2018

Other information: None.

Full text of H-statements:

H300	Fatal if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.
H360	May damage fertility or the unborn child.

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.